



啓盟工業股份有限公司
CHI MENG INDUSTRY CO.,LTD.

PE/EVA 發泡, L 系列產品物性表
PE/EVA Foam, L SERIES PHYSICAL PROPERTIES

項目 Items 品名 Articles	硬度 Hardness <i>ASTM D2240</i> SHORE C SHORE 00		延伸率 Elongation Ratio <i>ASTM D412</i> (%) ↑	抗張強度 Tensile Strength <i>ASTM D412</i> (kPa) ↑	撕裂強度 Tear Strength <i>ASTM D624</i> (kN/m) ↑	25%壓縮應力 Compression Strength 25% <i>ASTM D1056</i> (kPa) ↑	25%壓縮變型 Compression Set 25% <i>ASTM D1056</i> (%) ↓	密度 Density <i>ASTM D3575</i> (kg/m ³)	規格 Standard Size (mm)	備註 Note	
L-2500ULNH	16±3	30~45	200	170	1.0	20	32.0	24±3	1220*2440*87 1480*2440*87 1480*2440*76	UL94 HF1, ★	⊘
L-2500#2N	16±3	30~45	200	170	1.0	20	32.0	24±3	1000*2000*87 1000*2000*100	UL94 HF1	⊘
L-2500NN	16±3	30~45	200	170	1.0	20	32.0	24±3	1220*2440*87 1480*2440*87 1480*2440*76	CNS10487	⊘
L-2500	16±3	30~45	150	150	1.0	20	32.0	24±3	1480*2440*76		
L-1800	24±4	40~60	160	350	2.0	50	32.0	40±5	1000*2000*87		
L-1207	28±4	45~65	150	300	2.0	45	24.0	45±5	1200*2400*75		
L-0600	60±5	70~85	80	800	4.0	200	6.0	120±20	1000*2000*50		
★ : 無鹵, Halogen Free. ⊘ : 耐燃產品, Fire Retardant.											
										2025.01.20	

本表所提供之數值皆為代表值，並非保證值。

All given data should be considered as a guide, but can not be regarded as an engagement from our side.

www.chimeng.com.tw

sales@chimeng.com.tw