



啓盟工業股份有限公司
CHI MENG INDUSTRY CO.,LTD.

橡膠發泡, CR 系列產品物性表
Rubber Foam, CR SERIES PHYSICAL PROPERTIES

項目 Items 品名 Articles	硬度 Hardness <i>ASTM D2240</i> SHORE C SHORE 00		延伸率 Elongation Ratio <i>ASTM D412</i> (%) ↑	抗張強度 Tensile Strength <i>ASTM D412</i> (kPa) ↑	撕裂強度 Tear Strength <i>ASTM D624</i> (kN/m) ↑	25%壓縮應力 Compression Strength 25% <i>ASTM D1056</i> (kPa) ↑	25%壓縮變型 Compression Set 25% <i>ASTM D1056</i> (%) ↓	密度 Density <i>ASTM D3575</i> (kg/m ³)	規格 Standard Size (mm)	備註 Note	
CR-100NN	18±4	35~55	150	600	2.5	45	15.0	180±20	1000*1000*28	UL94 HF1	⊗
CR-250NN	26±4	42~62	150	800	2.9	50	15.0	180±20	1000*2000*30		⊗
⊗ : 耐燃產品, Fire Retardant.											2025.01.20

本表所提供之數值皆為代表值，並非保證值。

All given data should be considered as a guide, but can not be regarded as an engagement from our side.

www.chimeng.com.tw
sales@chimeng.com.tw