



啓盟工業股份有限公司
CHI MENG INDUSTRY CO.,LTD.

高彈性發泡, EL 系列產品物性表
High Elastic Foam, EL SERIES PHYSICAL PROPERTIES

項目 Items 品名 Articles	硬度 Hardness <i>ASTM D2240</i> SHORE C SHORE 00		延伸率 Elongation Ratio <i>ASTM D412</i> (%) ↑	抗張強度 Tensile Strength <i>ASTM D412</i> (kPa) ↑	撕裂強度 Tear Strength <i>ASTM D624</i> (kN/m) ↑	25%壓縮應力 Compression Strength 25% <i>ASTM D1056</i> (kPa) ↑	25%壓縮變型 Compression Set 25% <i>ASTM D1056</i> (%) ↓	密度 Density <i>ASTM D3575</i> (kg/m ³)	規格 Standard Size (mm)	備註 Note	
EL-300	10±3	20~40	300	250	1.5	20	25.0	30±10	1000*2000*100		
EL-180	10±3	20~40	200	300	2.0	20	50.0	40±5	1000*2000*73		
EL-1000	18±4	35~55	200	800	4.4	45	32.0	100±10	1100*2100*50		
2025.01.20											

本表所提供之數值皆為代表值，並非保證值。

All given data should be considered as a guide, but can not be regarded as an engagement from our side.

www.chimeng.com.tw

sales@chimeng.com.tw